



ST Series

Stagger Series

Application: This cost effective stagger strip light is ideal for use in most commercial areas. The unit is especially designed for display lighting where continuous mounting "black spots" are a problem.

Construction: This unit is designed from heavy gauge die formed steel and is finished in baked white enamel or polyester powder coating for maximum durability and reflectivity. Socket bar, end plate combination is riveted or screwed into fixture for maximum bulb support.


Electrical: All units are furnished with UL Listed Class P thermally protected ballast. Other voltages are available upon request. Fixtures meet requirements for UL Luminaire Standard # 1598. All units comply with National Energy Standards.

Mounting: Unit is equipped with provisions for surface or pendant mounting and installed in a continuous run. 7/8" knockout is provided in end plate for conduit connector.




Coefficients Utilization Zonal Cavity Method

RF	20										
	80%			70%			50%				
RC	70	50	30	10	70	50	30	10	50	30	10
0	102	102	102	102	98	98	98	98	89	89	89
1	91	86	82	78	87	83	79	75	76	72	70
2	82	74	67	62	78	71	65	60	65	60	56
3	75	65	57	51	71	62	55	49	57	51	46
4	68	57	48	42	64	54	47	41	50	44	39
5	62	50	41	35	58	48	40	34	44	37	32
6	56	44	36	30	54	42	35	29	39	32	27
7	52	39	31	26	49	38	30	25	35	28	24
8	48	35	27	22	45	33	26	21	31	25	20
9	44	32	24	19	42	30	23	18	28	22	17
10	41	29	21	16	39	28	21	16	25	19	15



Fixture Length

T12	T8	T5	T5HO	Length
F14T12	---	---	---	17 5/16"
F15T12	---	---	---	20 5/16"
F20T12	F17T8	F14T5	F24T5HO	26 5/16"
F30T12	F25T8	F21T5	F39T5HO	38 5/16"
F40T12	F32T8	F28T5	F54T5HO	50 5/16"



For Tandem Units:
Multiply lamp length above by lamp quantity

Maximum Weight = 9 lbs. / 50"

Ordering Information

Specifications Subject To Change Without Notice

Model	# Lamps	Lamp Type	Ballast	Voltage	Options	Cord	
ST-	2	32	E				
ST	2 = Two	<u>T12 Lamps</u> 14 = F14T12 15 = F15T12 20 = F20T12 30 = F30T12 40 = F40T12 <u>T8 Lamps</u> 17 = F17T8 25 = F25T8 32 = F32T8	<u>T5 Lamps</u> 14T5 = F14T5 21T5 = F21T5 28T5 = F28T5 <u>T5 High Output</u> 24T5HO = F24T5HO 39T5HO = F39T5HO 54T5HO = F54T5HO	M = Magnetic E = Electronic .88 BF E-LW = Electronic .77 BF E-O = Electronic 1.18 BF	Blank = 120V 277 = 277 V MV= Multi Volt	O = Grounded Outlet TOG = Toggle Switch ROC = Rocker Switch PULL = Pull Switch	CP-XE=Exit End CP-XS=Exit Side CP-XB=Exit Base Specify Cord Length
	22 = Double						