555 Series

Covered Wall Unit

Application: This covered wall unit is designed to provide maximum lumen output in areas such as hallways, bathrooms, kitchens, stairways, and hospitals. An assortment of options in either single or double lamp allows this utility wall and surface mounted unit to satisfy a variety of lighting needs.

Construction: Housing is designed from heavy gauge die formed steel and finished in either baked white enamel or polyester powder coating. Socket plate is riveted to housing adding to the structural support of the fixture. Lens is extruded white acrylic. End plates are attached by acorn nuts and secure the lens to the fixture.

Electrical: All units are furnished with UL Listed Class P thermally protected ballast. Other voltages are available upon request. Fixtures meet requirements for UL Luminaire Standard # 1598. All units comply with National Energy Standards.

Mounting: Unit is equipped with holes and 7/8" knockouts in housing for surface mounting. Fixture may be mounted individually or with optional joiner bands may be used in a continuous run.



Fixture Length

T12	T12HO	T8	Length
F15T12	---	---	**18"**
F20T12	---	F17T8	**24"**
F30T12	---	F25T8	**36"**
F40T12	F48T12HO	F32T8	**48"**



Maximum Weight = 12 lbs. / 48"

Ordering Information

Specifications Subject To Change Without Notice

Model	# Lamps	Lamp Type	Ballast	Voltage	Options
555-	**2**	**32**	**E**		
555	**1** = One **2** = Two	**T8 Lamps** **17** = F17T8 **25** = F25T8 **32** = F32T8 **T12 Lamps** **15** = F15T12 **20** = F20T12 **30** = F30T12 **40** = F40T12	**M** = Magnetic **E** = Electronic .88 BF **E-LW** =Electronic .77 BF **E-O** = Electronic 1.18 BF	**Blank** = 120V **277** = 277 V **MV**= Multi Volt	**O** = Grounded Outlet **TOG** = Toggle Switch **ROC =** Rocker Switch **PULL** = Pull Switch **EMB** = Emergency Ballast **NL** = Night Light **3WAY =** 3 W ay System

K-B Lighting Mfg. Co., Inc. 2101 Byberry Road, Philadelphia, PA 19116
(215) 673-6400 phone (215) 673-6431 fax sales@kblighting.com email